



Xyron® Pro 2500™

Product Specifications

Footprint	18.5" x 28.125" x 15" (47cm x 71.4cm x 38.1cm)
Weight/Packed Weight	90lbs (40.8kg) / 105lbs (47.6kg)
Document Thickness (max.)	0.10" (2.5mm) Up to 3/16" foam core with tray removed
Finished Document Width (max.)	25" (63.5cm)
Power Requirements	None
Cutter	Removable, replaceable cutter

The Xyron Pro 2500 is your complete professional document finishing system. Instantly applies laminate, adhesive or both without heat or electricity. Perfect for posters, displays, mock ups, banners and signs, advertisements, POP displays, and presentation-board.

Product Supply Description

- **Permanent High-Tack Adhesive:** Extremely aggressive adhesive instantly creates a permanent bond on most surfaces. Sets instantly and will not peel. Acid-Free.
- **Permanent Standard Adhesive:** Moderately aggressive adhesive creates a permanent bond on most surfaces. Can be touched to surface, peeled back quickly, and replaced. Acid-Free.
- **Repositionable Adhesive:** Allows items to be repositioned over and over. Easy removal from glass, walls, paper, and most other surfaces. Acid-Free.
- **Standard Use Laminate:** High-gloss film suitable for use on a variety of substrates. Superior adhesion. Compatible with most media. Acid-Free.
- **Thermal Print Sensitive Laminate:** High-gloss film suitable for use on thermal print sensitive items. Acid-Free.
- **Matte Laminate:** A high end clear laminate with minimal reflection. Acid-Free.
- ● **Combination—Laminate/Adhesive:** One of the laminate products described on the top surface and one of the acid-free adhesives described on the bottom surface. Acid-Free.

Part Number	Product Description	Material Length	Material Width	Laminate & Adhesive Combination Thickness (per side)	Mounting Adhesive Thickness	Adhesive pH	Mounting Adhesive Strength (1:10; 10-high)	PAT Approved
Adhesive Application Roll Set								
● AT400-300	Permanent High-Tack	300' (91.4m)	24.9' (63.4cm)	N/A	0.6mil (15.2mic)	Acid-Free	10	Yes
● AT405-300	Permanent Standard	300' (91.4m)	24.9' (63.4cm)	N/A	0.6mil (15.2mic)	Acid-Free	8	Yes
● AT406-170	Repositionable	170' (51.8m)	24.9' (63.4cm)	N/A	1.1mil (27.9mic)	Acid-Free	3	Yes
Lamination Cartridges								
● DL403-300	2-Sided Standard Use Laminate	300' (91.4m)	25.3' (64.3cm)	2.7mil (67.5mic)	N/A	Acid-Free	N/A	Yes
● DL404-300	2-Sided Thermal Print Sensitive Laminate General Use	300' (91.4m)	24.9' (63.4cm)	2.7mil (67.5mic)	N/A	Acid-Free	N/A	Yes
Combination One Side Laminate / One Side Adhesive Application								
● ● LAT405-300	1 Side Standard Use Laminate 1 Side High-Tack Adhesive	300' (91.4m)	25.3' (64.3cm)	2.7mil (67.5mic)	0.6mil (15.2mic)	Acid-Free	10	Yes
● ● MLAT405-300	1 Side Matte Laminate 1 Side High-Tack Adhesive	300' (91.4m)	25.3' (64.3cm)	2.7mil (67.5mic)	0.6mil (15.2mic)	Acid-Free	10	Yes

Xyron

**Cold Laminators,
Refill Cartridges &
Roll Sets**

Most product in stock
& shipped same day

BRIGHT WHITE PAPER CO.

To Order Call **800-321-5716**
Fax 772-223-4040
International 772-223-5511
P.O. Box 2472
Palm City, FL 34991

www.xyronpro.com | 1.800.793.3523

An **Esselte** Company